


Separate units ø 22: Heads

IP66
 To be combined with a clip, LED block and contact blocks (p. 48)
 With locking ring
 Plastic chrome bezel - Black bezel on request (form p. 79)
 Conform to IEC 60947-5-1

 Characteristics (p. 94)
 Cross reference list (p. 311)


► PUSH-BUTTONS - ILLUMINATED

SPRING RETURN - FLUSH

Cat. No.



L21AH20



Without engraving

- Red
- Green
- Yellow
- White
- Blue

L21AH10
L21AH20
L21AH40
L21AH50
L21AH60

On demand engraving (p. 79)

Symbol code to be added at the end of the catalogue number

- Red
- Green
- Yellow
- White
- Blue

L21AH31|_|_|_|
 L21AH32|_|_|_|
 L21AH34|_|_|_|
 L21AH35|_|_|_|
 L21AH36|_|_|_|

Without button plate

L21AH00


Button plates (p. 74)

SPRING RETURN - FLUSH

Reinforced degree of protection: IP 67



L22AP40



Supplied with transparent shroud


- Red
- Green
- Yellow
- White
- Blue

L22AP10
L22AP20
L22AP40
L22AP50
L22AP60

SPRING RETURN - SUPER FLUSH



L23AH10



Metallic chrome bezel
 Drilling ø 30 mm

Without engraving

- Red
- Green
- Yellow
- White
- Blue

L23AH10
L23AH20
L23AH40
L23AH50
L23AH60

On demand engraving (p. 79)

Symbol code to be added at the end of the catalogue number

- Red
- Green
- Yellow
- White
- Blue

L23AH31|_|_|_|
 L23AH32|_|_|_|
 L23AH34|_|_|_|
 L23AH35|_|_|_|
 L23AH36|_|_|_|

Catalogue No. in bold: normally in stock at distribution outlets